


Highlights:

- Flexible PVC jacket
- Stranded conductors
- H05VV-F

The PC3G15 and PC3G25 are high quality standard H05VV-F power cables for indoor and outdoor, fixed or mobile use. The cables are made of 3 PVC insulated conductors, with an inner section of 3x1.5mm² (PC3G15) or 3x2,5mm² (PC3G25). These cables can be used in damp spaces. Packed in a highly flexible PVC outer jacket of 8 mm resp. 9 mm. This offers you a cable that can be used in a wide variety of applications.



Inner Conductors:



Usage:



Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3 mm (Ø)
		Colours	Blue / Brown / Yellow & Green
Outer jacket	Material		Flexible PVC 8 mm (Ø)
	Colours		Black
Type of cable			3G1.5 PVC power cable
Inner conductor	Material		BC 48 x 0.2 mm (Ø) (OFC)
	Section		1.5 mm ²
	American Wire Gauge		16 AWG
	Number of conductors		3

Mechanical Characteristics:

Temperature range Fixed installation - 40 °C till + 80 °C

Flexible installation - 25 °C till + 60 °C

Bending radius Fixed installation 8 x outer diameter

Flexible installation 8 x outer diameter

Electrical Characteristics:

Lead resistance 1.2 Ω / 100 m

Max. current 16 Amp

Max. operation voltage 300 V